



ALEX YOKOHAMA CORPORATION, YOKOHAMA, JAPAN

Website: www.alex yokohama.com
E-mail: email@alex yokohama.com
Phone: + 8 1 - 4 5 - 9 4 9 - 5 5 1 1



“CORONA” Kerosene Heater



Portable Kerosene Heater



Kerosene Fan Heater

SPECIFICATION LIST



PRODUCT SPECIFICATIONS

1) DIMENSIONS (H) × (W) × (D)	cm	39.0 × 31.2 × 30.7 (base plate included)
2) NET WEIGHT	kg	8.5
3) POWER SOURCE		Single phase / 230V / 50Hz
4) HEATER TYPE		Gasification type fan heater
5) HEATING OUTPUT	kW	2.47 ~ 0.81
	BTU/h	8,400 ~ 2,750
	kcal/h	2,120 ~ 690
6) FUEL CONSUMPTION RATE	liter/h	0.240 ~ 0.078
7) FUEL TANK CAPACITY	liter	4.0
8) CONTINUOUS HOURS OF HEATING		Approx. min. 16.6 ~ max. 51.2 hours
9) RATED POWER CONSUMPTION	W	16.0

PACKING SPECIFICATIONS

1) PACKING		One unit – One carton box
2) PACKING DIMENSIONS (H) × (W) × (D)	cm	45.5 × 36.4 × 35.4
3) SHIPPING WEIGHT	kg	9.5 (Estimated weight)
4) Q'TY IN EACH CONTAINER (PCS)	20 ft	480
	40 ft	990 *The same quantity of heater can be loaded by dry and HC container.

FEATURES

1) ANTI SHOCK AUTOMATIC SHUT-OFF DEVICE	Yes
2) OVERHEAT PREVENTION DEVICE	Yes
3) SAFE IGNITION SYSTEM	Yes
4) FLAME CONDITION MONITOR	Yes
5) POWER FAILURE SAFETY DEVICE	Yes
6) PREVENTION SYSTEM FOR IMPERFECT COMBUSTION	Yes
7) TYPE OF FUEL TANK	Removable Cartridge
8) BASE COLOUR	Black

SPECIFICATION LIST

ARTICLE	KEROSENE FAN HEATER	MODEL	FH-5005
CORONA™			
			
PRODUCT SPECIFICATIONS			
1) DIMENSIONS (H) × (W) × (D)	cm	45.4 × 40.0 × 30.9 (base plate included)	
2) NET WEIGHT	kg	9.5	
3) POWER SOURCE		Single phase / 230V / 50Hz	
4) HEATER TYPE		Gasification type fan heater	
5) HEATING OUTPUT	kW	3.44 ~ 0.86	
	BTU/h	11,700 ~ 2,950	
	kcal/h	2,960 ~ 740	
6) FUEL CONSUMPTION RATE	liter/h	0.334 ~ 0.084	
7) FUEL TANK CAPACITY	liter	5.0	
8) CONTINUOUS HOURS OF HEATING		Approx. min. 15.0 ~ max. 59.5 hours	
9) RATED POWER CONSUMPTION	W	22.0	
PACKING SPECIFICATIONS			
1) PACKING		One unit - One carton box	
2) PACKING DIMENSIONS (H) × (W) × (D)	cm	52.0 × 45.0 × 35.4	
3) SHIPPING WEIGHT	kg	11.5	
4) Q'TY IN EACH CONTAINER (PCS)	20 ft	332	
	40 ft	680 (Dry)	
		850 (HC)	
FEATURES			
1) ANTI SHOCK AUTOMATIC SHUT-OFF DEVICE		Yes	
2) OVERHEAT PREVENTION DEVICE		Yes	
3) SAFE IGNITION SYSTEM		Yes	
4) FLAME CONDITION MONITOR		Yes	
5) POWER FAILURE SAFETY DEVICE		Yes	
6) PREVENTION SYSTEM FOR IMPERFECT COMBUSTION		Yes	
7) TYPE OF FUEL TANK		Removable Cartridge	
8) BASE COLOUR		Gray	



SPECIFICATION LIST

ARTICLE	KEROSENE FAN HEATER	MODEL	FH-6003
CORONA™			
			
PRODUCT SPECIFICATIONS			
1) DIMENSIONS (H) × (W) × (D)	cm	45.4 × 43.4 × 31.3 (base plate included)	
2) NET WEIGHT	kg	10.0	
3) POWER SOURCE		Single phase / 230V / 50Hz	
4) HEATER TYPE		Gasification type fan heater	
5) HEATING OUTPUT	kW	4.28 ~ 0.86	
	BTU/h	14,600 ~ 2,950	
	kcal/h	3,680 ~ 740	
6) FUEL CONSUMPTION RATE	liter/h	0.416 ~ 0.084	
7) FUEL TANK CAPACITY	liter	5.0	
8) CONTINUOUS HOURS OF HEATING		Approx. min. 12.0 ~ max. 59.5 hours	
9) RATED POWER CONSUMPTION	W	21.0 ~ 12.0	
PACKING SPECIFICATIONS			
1) PACKING		One unit - One carton box	
2) PACKING DIMENSIONS (H) × (W) × (D)	cm	53.5 × 48.5 × 36.0	
3) SHIPPING WEIGHT	kg	12.0 (Estimated weight)	
4) Q'TY IN EACH CONTAINER (PCS)	20 ft	300	
	40 ft	624 (Dry)	
		771 (HC)	
FEATURES			
1) ANTI SHOCK AUTOMATIC SHUT-OFF DEVICE		Yes	
2) OVERHEAT PREVENTION DEVICE		Yes	
3) SAFE IGNITION SYSTEM		Yes	
4) FLAME CONDITION MONITOR		Yes	
5) POWER FAILURE SAFETY DEVICE		Yes	
6) PREVENTION SYSTEM FOR IMPERFECT COMBUSTION		Yes	
7) TYPE OF FUEL TANK		Removable Cartridge	
8) BASE COLOUR		Gray	

SPECIFICATION LIST

ARTICLE	KEROSENE FAN HEATER	MODEL	FH-6740
CORONA™			
			
PRODUCT SPECIFICATIONS			
1) DIMENSIONS (H) × (W) × (D)	cm	42.6 × 50.4 × 33.4 (base plate included)	
2) NET WEIGHT	kg	13.0	
3) POWER SOURCE		Single phase / 230V / 50Hz	
4) HEATER TYPE		Gasification type fan heater	
5) HEATING OUTPUT	kW	4.28 ~ 1.07	
	BTU/h	14,600 ~ 3,650	
	kcal/h	3,680 ~ 920	
6) FUEL CONSUMPTION RATE	liter/h	0.416 ~ 0.104	
7) FUEL TANK CAPACITY	liter	7.2	
8) CONTINUOUS HOURS OF HEATING		Approx. min. 16.8 ~ max. 67.3 hours	
9) RATED POWER CONSUMPTION	W	23.0	
PACKING SPECIFICATIONS			
1) PACKING		One unit - One carton box	
2) PACKING DIMENSIONS (H) × (W) × (D)	cm	49.5 × 56.0 × 39.0	
3) SHIPPING WEIGHT	kg	14.1 (Estimated weight)	
4) Q'TY IN EACH CONTAINER (PCS)	20 ft	240	
	40 ft	504 (Dry)	
		630 (HC)	
FEATURES			
1) ANTI SHOCK AUTOMATIC SHUT-OFF DEVICE		Yes	
2) OVERHEAT PREVENTION DEVICE		Yes	
3) SAFE IGNITION SYSTEM		Yes	
4) FLAME CONDITION MONITOR		Yes	
5) POWER FAILURE SAFETY DEVICE		Yes	
6) PREVENTION SYSTEM FOR IMPERFECT COMBUSTION		Yes	
7) TYPE OF FUEL TANK		Removable Cartridge	
8) BASE COLOUR		Gray	

SPECIFICATION LIST

ARTICLE	KEROSENE FAN HEATER	MODEL	FH-7740
			
			
PRODUCT SPECIFICATIONS			
1) DIMENSIONS (H) × (W) × (D)	cm	42.6 × 50.4 × 33.4 (base plate included)	
2) NET WEIGHT	kg	13.0	
3) POWER SOURCE		Single phase / 230V / 50Hz	
4) HEATER TYPE		Gasification type fan heater	
5) HEATING OUTPUT	kW	4.99 ~ 1.07	
	BTU/h	17,000 ~ 3,650	
	kcal/h	4,290 ~ 920	
6) FUEL CONSUMPTION RATE	liter/h	0.485 ~ 0.104	
7) FUEL TANK CAPACITY	liter	7.2	
8) CONTINUOUS HOURS OF HEATING		Approx. min. 14.4 ~ max. 67.3 hours	
9) RATED POWER CONSUMPTION	W	24.0	
PACKING SPECIFICATIONS			
1) PACKING		One unit - One carton box	
2) PACKING DIMENSIONS (H) × (W) × (D)	cm	49.5 × 56.0 × 39.0	
3) SHIPPING WEIGHT	kg	14.1 (Estimated weight)	
4) Q'TY IN EACH CONTAINER (PCS)	20 ft	240	
	40 ft	504 (Dry)	
		630 (HC)	
FEATURES			
1) ANTI SHOCK AUTOMATIC SHUT-OFF DEVICE		Yes	
2) OVERHEAT PREVENTION DEVICE		Yes	
3) SAFE IGNITION SYSTEM		Yes	
4) FLAME CONDITION MONITOR		Yes	
5) POWER FAILURE SAFETY DEVICE		Yes	
6) PREVENTION SYSTEM FOR IMPERFECT COMBUSTION		Yes	
7) TYPE OF FUEL TANK		Removable Cartridge	
8) BASE COLOUR		Gray	

SPECIFICATION LIST

ARTICLE	PORTABLE KEROSENE HEATER	MODEL	RX-29W
CORONA™			
			

PRODUCT SPECIFICATIONS

1) DIMENSIONS (H) × (W) × (D)	cm	46.7 × 61.8 × 32.4
2) NET WEIGHT	kg	9.1
3) HEATER TYPE		Radiant
4) HEATING OUTPUT	kW	2.87 ~ 2.29
	BTU/h	9,800 ~ 7,800
	kcal/h	2,470 ~ 1,970
5) FUEL CONSUMPTION RATE	liter/h	0.279 ~ 0.223
6) FUEL TANK CAPACITY	liter	5.0
7) CONTINUOUS HOURS OF HEATING		Approx. min. 17.9 ~ max. 22.4 hours


PACKING SPECIFICATIONS

1) PACKING		One unit – One carton box
2) PACKING DIMENSIONS (H) × (W) × (D)	cm	51.5 × 67.0 × 38.5
3) SHIPPING WEIGHT	kg	11.0
4) Q'TY IN EACH CONTAINER (PCS)	20 ft	204
	40 ft	420 (Dry) 525 (HC)

FEATURES

1) AUTI SHOCK AUTOMATIC SHUT-OFF DEVICE	Yes
2) BATTERY IGNITION SYSTEM	Yes (Ignition of the wick without tilting the burner)
3) TYPE OF FUEL TANK	Removable Cartridge
4) WICK	Glass wool
5) BASE COLOR	Dark wooden grain

SPECIFICATION LIST

ARTICLE	PORTABLE KEROSENE HEATER	MODEL	SL-51
CORONA™			
			
PRODUCT SPECIFICATIONS			
1) DIMENSIONS (H) × (W) × (D)	cm	55.3 × 46.0 × 46.0	
2) NET WEIGHT	kg	9.9	
3) HEATER TYPE		Convection	
4) HEATING OUTPUT	kW	5.14	
	BTU/h	17,600	
	kcal/h	4,420	
5) FUEL CONSUMPTION RATE	liter/h	0.500	
6) FUEL TANK CAPACITY	liter	6.0	
7) CONTINUOUS HOURS OF HEATING		Approx. 12.0 hours	
PACKING SPECIFICATIONS			
1) PACKING		One unit – One carton box	
2) PACKING DIMENSIONS (H) × (W) × (D)	cm	57.6 × 49.0 × 44.4	
3) SHIPPING WEIGHT	kg	12.4	
4) Q'TY IN EACH CONTAINER (PCS)	20 ft	220	
	40 ft	480 *The same quantity of heater can be loaded by dry and HC container.	
FEATURES			
1) ANTI SHOCK AUTOMATIC SHUT-OFF DEVICE		Yes	
2) BATTERY IGNITION SYSTEM		Yes	
3) TYPE OF FUEL TANK		Integral	
4) FUEL GAUGE		Yes	
5) WICK		Glass wool	
6) BASE COLOR		White	

SPECIFICATION LIST

ARTICLE	PORTABLE KEROSENE HEATER	MODEL	SL-66
			CORONA™
PRODUCT SPECIFICATIONS			
1) DIMENSIONS (H) x (W) x (D)	cm	59.8 x 46.0 x 46.0	
2) NET WEIGHT	kg	11.2	
3) HEATER TYPE		Convection	
4) HEATING OUTPUT	kW	6.59	
	BTU/h	22,500	
	kcal/h	5,670	
5) FUEL CONSUMPTION RATE	liter/h	0.640	
6) FUEL TANK CAPACITY	liter	7.0	
7) CONTINUOUS HOURS OF HEATING		Approx. 10.9 hours	
PACKING SPECIFICATIONS			
1) PACKING		One unit – One carton box	
2) PACKING DIMENSIONS (H) x (W) x (D)	cm	62.6 x 51.0 x 49.0	
3) SHIPPING WEIGHT	kg	14.4	
4) Q'TY IN EACH CONTAINER (PCS)	20 ft	132	
	40 ft	288 (Dry)	
		384 (HC)	
FEATURES			
1) ANTI SHOCK AUTOMATIC SHUT-OFF DEVICE		Yes	
2) BATTERY IGNITION SYSTEM		Yes	
3) TYPE OF FUEL TANK		Integral	
4) FUEL GAUGE		Yes	
5) WICK		Glass wool	
6) BASE COLOR		White	

SPECIFICATION LIST

ARTICLE	PORTABLE KEROSENE HEATER	MODEL	SX-248
CORONA™			
			
PRODUCT SPECIFICATIONS			
1) DIMENSIONS (H) × (W) × (D)	cm	47.5 × 45.2 × 31.4	
2) NET WEIGHT	kg	7.3	
3) HEATER TYPE		Radiant	
4) HEATING OUTPUT	kW	2.42 ~ 1.93	
	BTU/h	8,250 ~ 6,600	
	kcal/h	2,080 ~ 1,660	
5) FUEL CONSUMPTION RATE	liter/h	0.235 ~ 0.188	
6) FUEL TANK CAPACITY	liter	4.0	
7) CONTINUOUS HOURS OF HEATING		Approx. min. 17.0 ~ max. 21.3 hours	
PACKING SPECIFICATIONS			
1) PACKING		One unit – One carton box	
2) PACKING DIMENSIONS (H) × (W) × (D)	cm	52.6 × 49.2 × 35.4	
3) SHIPPING WEIGHT	kg	8.2	
4) Q'TY IN EACH CONTAINER (PCS)	20 ft	300	
	40 ft	624 *The same quantity of heater can be loaded by dry and HC container.	
FEATURES			
1) ANTI SHOCK AUTOMATIC SHUT-OFF DEVICE		Yes	
2) BATTERY IGNITION SYSTEM		Yes (Ignition of the wick without tilting the burner)	
3) TYPE OF FUEL TANK		Removable Cartridge	
4) WICK		Glass wool	
5) BASE COLOR		Dark blue	

SPECIFICATION LIST

ARTICLE	PORTABLE KEROSENE HEATER	MODEL	SX-288
CORONA™			
			
PRODUCT SPECIFICATIONS			
1) DIMENSIONS (H) × (W) × (D)	cm	51.0 × 45.2 × 31.4	
2) NET WEIGHT	kg	7.4	
3) HEATER TYPE		Radiant	
4) HEATING OUTPUT	kW	2.83 ~ 2.26	
	BTU/h	9,700 ~ 7,700	
	kcal/h	2,430 ~ 1,940	
5) FUEL CONSUMPTION RATE	liter/h	0.275 ~ 0.220	
6) FUEL TANK CAPACITY	liter	4.0	
7) CONTINUOUS HOURS OF HEATING		Approx. min. 14.5 ~ max. 18.2 hours	
PACKING SPECIFICATIONS			
1) PACKING		One unit – One carton box	
2) PACKING DIMENSIONS (H) × (W) × (D)	cm	56.1 × 49.2 × 35.4	
3) SHIPPING WEIGHT	kg	8.4	
4) Q'TY IN EACH CONTAINER (PCS)	20 ft	300	
	40 ft	624 *The same quantity of heater can be loaded by dry and HC container.	
FEATURES			
1) ANTI SHOCK AUTOMATIC SHUT-OFF DEVICE		Yes	
2) BATTERY IGNITION SYSTEM		Yes (Ignition of the wick without tilting the burner)	
3) TYPE OF FUEL TANK		Removable Cartridge	
4) WICK		Glass wool	
5) BASE COLOR		Dark blue	